## ►LINDSTRÖM<sup>®</sup>

## RX 8156

ERGO<sup>™</sup> Micro-Bevel® Precision Cut Diagonal Cutter with Tapered & Relieved Head 0.3-1.25 mm



## PRODUCT DETAILS


- Precision extra tapered & relieved head diagonal cutters developed according to the scientific ERGO™ process
- Extra Tapered & relieved head
- ERGO<sup>™</sup> handles with two-component combination, thermoplastic surface, for comfortable grip, on tough polypropylene core for rigidity
- Flush & ultra-flush
- The cutting capacity that is given is for copper wire
- Cutting capacity: 0.1 mm-0.8 mm
- High performance alloyed steel

Burnished finish

• Numerically controlled machine grinding guarantees edge angle accuracy & contact, increases the tool's reliability & consistency

- Precision induction-hardened edges 63-65 HRC
- Screw joint minimises friction & maximises alignment of cutting edges
- ESD safe handles in two-component synthetic material
- Bio spring limits the tension throughout the working cycle of the tool & can be adjusted to 3 different positions or removed
- Ideal for use in confined spaces & for rework thanks to the thinner tip head





Product: RX 8156					
	Tapered & Relieved	< \$	М		Micro-Bevel ®
	0.3-1.25 mm		0.01-0.05 in	Α	138 mm
Α	5.30 in	Β	13 mm	Β	0.51 in
С	12.5 mm	С	0.49 in	D	6 mm
D	0.24 inch	F	1.2 mm	F	0.05 in
g	70 g	Ω	Dissipative		