►LINDSTRÖM[®]

MAL500-1D Micro-Adjustable Torque Screwdriver 16 cN.m-80 cN.m




PRODUCT DETAILS

- ESD safe (IEC 61340-5-1)
- Torque limiting clutch prevents over application of force to fastener
- 1/4" Hexagon anti-magnetic spring loaded bit holder to avoid ESD damage to sensitive equipment or components in electronic applications
- Adjustable Torque Screwdriver, with all metal 3-lobe shaped handle
- Powder coat wrinkle finish provides positive grip
- Cam-over torque limiting clutch for repeatability
- Store driver in the protective case at lowest torque setting

- Accuracy meets or exceeds +/-6% over recommended usage period: 5.000 cycles or one year, whichever occurs first
- Clockwise torque measurement only. It can be used to loosen fasteners without affecting the internal mechanism
- Cam-Over technology provides tactile and audible feedback when torque values are reached
- Supplied with an internal declaration of conformity in compliance with International standards.
- Standard adjustable drivers include window with single scale in cNm
- ISO 6789, ISO 1174, ASME B107.300-2010
- Made in USA







| Product: MAL500-1D | | | | |
|--------------------|---|--|--|--|
| 16-80 cNM | inaz | 20-200 ozf.in | ill.l.l.l.l.l.l.l.l.l.l.l.l.l.l.l.l.l.l | |
| 1/4 in | dN-M | 1 cNM | Α | 138 mm |
| 5.43 in | B | 18.2 mm | Β | 0.72 in |
| 28 mm | С | 1.10 in | D | 9.6 mm |
| 0.38 in | kg | 0.2 kg | | |
| | 16-80 cNM 1/4 in 5.43 in 28 mm | 16-80 cNM Image: Compare the second seco | 16-80 cNM 20-200 ozf.in 1/4 in 1 cNM 5.43 in B 18.2 mm 28 mm 1.10 in | 16-80 cNM 20-200 ozf.in 1/4 in 1 cNM 5.43 in B 28 mm C 1.10 in |