## ►LINDSTRÖM<sup>®</sup>

## **RX-8168**


Ergo™ Ultra-Flush® Precision Cut Diagonal Cutter with Tapered & Relieved Head 0.3-1.25 mm



## PRODUCT DETAILS

- Ideal for use in confined spaces and for rework
- Two-component Ergo<sup>™</sup> handles: thermoplastic surface on tough polypropylene provides superior grip
- Material: High performance alloy steel
- Precision induction hardened cutting edges to 63–65 HRC
- ESD safe handles in 2-component synthetic material
- Micro-Touch<sup>™</sup>: The shape of the handles makes it possible to control and rotate the pliers between thumb and index finger for precision work
- Precision screw joint that minimizes friction and maximizes alignment of cutting edges
- Biospring® reduces tension throughout the working cycle of the tool and can be adjusted in three different positions
- Cutting capacity is listed for solid copper wire
- Phosphated finish





Product: RX-8168					
	Tapered & Relieved	< \$	L	Α	147.0 mm
A	5.80 in	Β	16 mm	Β	0.63 in
С	16 mm	С	0.63 in	D	8 mm
D	0.31 inch	F	1.6 mm	F	0.06 in
(P)	0.3-1.25 mm		0.01-0.05 in		Ultra-Flush ®
g	139 g	Ω	Dissipative		